SUNLIFE POWER

Li - ion Battery 12.8 V 300 Ah

SUNLIFE POWER

12.8V 300Ah










LFP Li-ion Battery



Dimension:



SAFETY

- Prismatic LiFePO4 cells (100Ah), High consistency, long cycle life and much more safety. UN38.3, CE certification for system.
- The cycle life over 3500 times @80%DOD

DESIGN

- ABS container, replace VRLA battery perfectly.
- Fast charge performance.
- -20~+55° C widely temperature range.
- + Maintenance free.

BATTERY MANAGEMENT SYSTEM (BMS)

- Integrated hardware BMS inside.
- Independent protection for charge and discharge.
- Over voltage, low voltage, over temperature and short circuit protection.

Unit: mm

12.8V300Ah

Specification

Li-ion Battery

| Specification | |
|----------------------------------|--|
| Model | R-LFP12.8V300Ah |
| Part Number | 8010128030001 |
| Nominal Voltage [V] | 12.8 |
| Nominal Capacity [Ah] | 300 |
| Total Energy [Wh] | 3840 |
| Max. Charging Current [A] | 100 |
| Recommended Charging Current [A] | 80 |
| Charging Voltage [V] | 14.6 |
| Max. Discharging Current [A] | 100 |
| End of Dicharge Voltage [V] | 11.2 |
| Pulse Discharge Current | 270A @ 10s |
| Dimension [W*D*H, mm] | 522*268*220 |
| Weight [Kg] | 32.00 |
| Operation Humidity | 0~95% RH (No condensing) |
| Operating Temperature Range | Charge: 0 ~ +50 °C; Discharge: -20 ~ +55 °C |
| BMS Protection | Over charge Over discharge, Over temperature, Short circuit |
| Parallel Support | Yes, Max 2 Sets |
| Series Support | Yes, Max 4 Sets |
| Cycle Life | >3500 |
| Designed Calendar Life | >10 Years |
| Certification | UN38.3, CE, MSDS |
| | |

1. 80% DOD and to 80% of initial capacity.